FORM PTO-1390 U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE (REV 10.95)

ATTORNEY'S DOCKET NUMBER
450118-02330

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371

U S APPLICATION NO. (If known see 37 C.F.R. 1.5)
09/647964

INTERNATIONAL APPLICATION NO	INTERNATIONAL FILING DATE	(EARLIEST) PRIORITY DATE CLAIMED
PCT/JP00/00705	**9 February 2000**	**9 February 1999**

TITLE OF INVENTION: **INFORMATION DISTRIBUTION SYSTEM AND METHOD, TERMINAL APPARATUS, SERVER APPARATUS, DATA RECEPTION METHOD, AND DATA TRANSMISSION METHOD**

APPLICANTS FOR DO/EO/US: **Kazuyuki SAKODA and Mitsuhiro SUZUKI**

Applicants herewith submit to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
   a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
   b. ☒ has been transmitted by the International Bureau.
   c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)), including **8** sheets of formal drawings and a copy of the International Search Report.
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
   a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
   b. ☐ have been transmitted by the International Bureau.
   c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
   d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventors (35 U.S.C. 371(c)(4)).
10. ☐ The annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A FIRST preliminary amendment.
    ☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:
    PCT/IB/301, 304, 308
    PCT/RO/101
    References for IDS

EXPRESS MAIL
Mailing Label Number: EL588273186US
Date of Deposit: October 6, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" Service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents and Trademarks, Box PCT Washington, DC 20231.

S. Abdulsattar
(Typed or printed name of person mailing paper or fee)
S. Abdulsattar
(Signature of person mailing paper or fee)

528 Rec'd PCT/PTO 06 OCT 2000

U.S. APPLICATION NO.(If known, see 37 C.F.R. 1.50) 09/647964 | INTERNATIONAL APPLICATION NO PCT/JP00/00705 | ATTORNEY'S DOCKET NO. 450118-02330

17. ☒ The following fees are submitted: (CALCULATIONS /PTO USE ONLY

Basic National Fee (37 CFR 1.492(a)(1)-(5):

Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37CFR 1.445(a)(2) paid to USPTO and International Search Report not prepared by the EPO or JPO... ... $1000.00

International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO.....$ 860.00

International preliminary examination fee paid to USPTO (37 CFR 1.482) Not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO (37 CFR 1.445(a)(2))....$ 710.00

International preliminary examination fee paid to USPTO (37 CFR 1.482) But all claims did not satisify provisions of PCT Article 33(1)-(4).....$ 690.00

International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4).....$ 100.00

ENTER APPROPRIATE BASIC FEE AMOUNT = ($860.00

Surcharge of **$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(e)). ($ /

47 Claims	/Number Filed	/	Number Extra	/Rate	(
Total Claims	/ 47 - 20 =	/	27	/X $18.00	($ 486.00
Independent Claims	/ 6 - 3 =	/	3	/X $80.00	($ 240.00
Multiple dependent claim(s) (if applicable)				/+ $260.00	($

TOTAL OF ABOVE CALCULATIONS = ($ 1,586.00

Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity (/ statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28). (/

SUBTOTAL = **($ 1,586.00**

Processing fee of **$130.00** for furnishing the English translation later than (/ ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(f)).+ ($ /

TOTAL NATIONAL FEE = ($ 1,586.00

Fee for recording the enclosed assignments (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). **$40.00** per property + ($ / ($ /

TOTAL FEES ENCLOSED = ($ 1,586.00

(Amount to be: / (refunded /$

(charged /$

a. ☒ Our check in the amount of **$1,586.00** to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. 50-0320 in the amount of $_____ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. **50-0320**. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

WILLIAM S. FROMMER
FROMMER LAWRENCE & HAUG LLP
745 FIFTH AVENUE
NEW YORK, NEW YORK 10151

Dated: October 6, 2000

SIGNATURE

WILLIAM S. FROMMER
NAME

25,506
REGISTRATION NUMBER

Form PTO-1390 (REV **10-96**)
SA0111

DESCRIPTION

INFORMATION DISTRIBUTION SYSTEM AND METHOD, TERMINAL APPARATUS, SERVER APPARATUS, DATA RECEPTION METHOD, AND DATA TRANSMISSION METHOD

TECHNICAL FIELD

The present invention relates to an information distribution system and method, a terminal apparatus, a server apparatus, a data reception method, and a data transmission method able to be applied to a network system such as a cellular wireless communication system and particularly capable of averaging a traffic load over time and efficiently utilizing a communication infrastructure.

BACKGROUND ART

As an example of a general communication system for distributing information in the related art, web browsing over the Internet can be mentioned.

A communication procedure in web browsing of the related art is shown in Fig. 1.

In this procedure, when a terminal station sends a demand for provision of information (demand for content) to a contents server, the contents server immediately

responds to this and transmits the requested information content (requested content) to the terminal station.

In the above communication system, however, since it is based on real-time communication immediately responding to a request for providing information, for example as shown in Fig. 2, the traffic load widely varies such as with the amount sharply increasing during a certain time band and oppositely the amount largely decreasing during a time band, for example, at the night.

Accordingly, it suffers from the disadvantage that communication facilities are not in use during the night time and other time bands when the communication traffic is low, so the communication facilities are not efficiently used.

Further, it suffers from the disadvantage of the difficulty in sufficient improvement of the efficiency of utilization of the communication facilities because a network operator often determines a traffic load of a communication system in order to provide an acceptable quality of service during the time bands when the traffic load is large.

DISCLOSURE OF THE INVENTION

An object of the present invention is to provide an information distribution system and method capable of

averaging a traffic load over time and efficiently utilizing communication facilities.

Another object of the present invention is to provide an (a) terminal apparatus, (b) server apparatus, (c) data reception method, and (d) data transmission method used for such an information distribution system and capable of contributing to the averaging of the traffic load in the network and efficient utilization of communication facilities.

According to a first aspect of the present invention, there is provided an information distribution system transmitting information based on a demand from a terminal apparatus from a server apparatus to the terminal apparatus, wherein said server apparatus comprises a first transceiver for transmission to the terminal apparatus and a first controller for scheduling a point of time for distribution based on a state of a communication line used for distribution of information in accordance with a request signal requesting information from the terminal apparatus received at said transceiver and controlling the system for distribution of information for said request signal to the terminal apparatus through the transceiver at the scheduled point of time and said terminal apparatus comprises a second transceiver for communication with a server apparatus and

a second controller for generating a request signal for requesting the distribution of desired information, controlling the system for transmission of the requested information to said server through said second transceiver, and controlling the system for reception of said information distributed by said server apparatus in a period of time determined by said server apparatus with respect to said request signal.

According to a second aspect of the present invention, there is provided a terminal apparatus receiving distribution of information from a server apparatus, said terminal apparatus receiving distribution of information from a server apparatus comprising a transceiver for transmission to the server apparatus and a controller for generating a request signal for requesting the distribution of desired information, controlling the system for transmission of the requested information to said server through said transceiver, and controlling the system for reception of said information distributed by said server apparatus in a period of time determined by said server apparatus with respect to said request signal.

According to a third aspect of the present invention, there is provided a server apparatus transmitting information based on a demand from a

terminal apparatus, said server apparatus transmitting information based on a demand from a terminal apparatus comprising a transceiver for transmission to the terminal apparatus and a controller for scheduling a point of time for distribution based on a state of a communication line used for distribution of information in accordance with a request signal requesting information from the terminal apparatus received at said transceiver and controlling the system for distribution of information for said request signal to the terminal apparatus through the transceiver at the scheduled point of time.

According to a fourth aspect of the present invention, there is provided an information distribution method for transmitting information based on a request from a terminal apparatus from a server apparatus to the terminal apparatus, said information distribution method for transmitting information based on a request from a terminal apparatus from a server apparatus to the terminal apparatus comprising the steps of having said terminal apparatus generates a request signal requesting distribution of desired information; transmitting said request signal from said terminal apparatus to said server; having said server apparatus schedule a point of time for distribution based on a state of a communication line to be used for the distribution of information in

accordance with a request signal requesting information from said terminal apparatus; distributing information for said request signal from said server apparatus to said terminal apparatus at the scheduled point of time; and having said terminal apparatus receive said information distributed from said server apparatus.

According to a fifth aspect of the present invention, there is provided a data reception method for receiving distribution of information from a server apparatus, said data reception method for receiving distribution of information from a server apparatus comprising the steps of generating a request signal requesting distribution of desired information; transmitting said requested information to said server; and receiving said information distributed by said server apparatus in a period of time determined by said server apparatus for said request signal.

According to a sixth aspect of the present invention, there is provided a data transmission method for transmitting information based on a request from a terminal apparatus, said data transmission method for transmitting information based on a request from a terminal apparatus comprising the steps of receiving a request signal requesting information from a terminal apparatus; scheduling a point of time for distribution

based on a state of a communication line used for distribution of information; and transmitting the information for the request signal to the terminal apparatus at the scheduled point of time.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a view of a communication procedure in a communication system for performing conventional general information distribution.

Figure 2 is a view of fluctuations in a traffic load over a day in a conventional general communication system.

Figure 3 is a view of a network configuration of a cellular wireless communication system of an embodiment of the present invention.

Figure 4 is a block diagram of the configuration of a contents server of the cellular wireless communication system shown in Fig. 3.

Figure 5 is a block diagram of the configuration of a terminal station of the cellular wireless communication system shown in Fig. 3.

Figure 6 is a view of a basic procedure of information distribution in the cellular wireless communication system shown in Fig. 3.

Figure 7 is a view of fluctuations in a traffic load

over a day in the cellular wireless communication system shown in Fig. 3.

BEST MODE FOR CARRYING OUT THE INVENTION

First Embodiment

An embodiment of the present invention will be explained with reference to Figs. 3 to 7.

In the present embodiment, the present invention will be explained by giving as an example a cellular wireless communication system.

First, the network configuration of a cellular wireless communication system of the present embodiment will be explained with reference to Fig. 3.

Figure 3 is a view of the network configuration of the cellular wireless communication system of the present embodiment.

A cellular wireless communication system 1 of the present embodiment has the configuration of arranging in layers as shown in the figures a contents server 10, a plurality of network nodes 20_{-1} to 20_{-n}, and a plurality of terminal stations 30_{-1} to 30_{-m}. Information is transmitted from the contents server 10 to the respective terminal stations 30_{-j} (j=1 to m) via the network nodes 20_{-i} (i=1 to n).

In the cellular wireless communication system 1, the network nodes 20_{-1} to 20_{-n} correspond to an MTSO (Mobile

Telephone Switching Office) or a wireless base station CS (Cell Site) etc. Therefore, communication between the network nodes 20_{-i} (i=1 to n) and the terminal stations 30_{-j} is maintained by the control carried out in an existing cellular wireless communication system.

The parts of the cellular wireless communication system 1 will be explained in further detail below.

The contents server 10 is a server apparatus storing desired information to be distributed and suitably distributes it in accordance with requests. The contents server 10 is specifically configured by, for example, a work station and a file server apparatus having a communication interface.

The contents server 10 has a processing module for realizing functions related to information distribution described below and thereby performs desired processing.

First, the contents server 10 receives a distribution request of any information transmitted from the respective terminal stations 30_{-j} of the cellular wireless communication system 1 shown in Fig. 3. The distribution request includes contents information for specifying information requested, terminal information for specifying a terminal station 30_{-j} and time limit information indicating a time limit of distribution.

When receiving a distribution request, the contents

server 10 judges whether or not it has the information requested and judges whether it is possible to distribute the information before the time indicated by the time limit information and thereby detects whether it can respond to the distribution request and notifies the results to the terminal station 30_{-j}.

Further, when it is found to be possible to distribute the desired information by this, the server refers to the information of the traffic load of the network estimated and stored in advance to calculate the period of time where the traffic load of the network is small and thereby determines the period of time for distribution of the information, notifies this to the terminal station 30_{-j}, and stores this as a distribution schedule in the contents server 10.

Then, the contents server 10 successively distributes the information to the terminal station 30_{-j} in accordance with this stored distribution schedule.

Further, at the time of the information distribution, the contents server 10 performs processing for charging the respective terminal stations 30_{-j} for the distribution of information. The charge for the distributed information is determined by a variety of conditions such as the type or amount of the distributed information, the content of contracts for the information

distribution service, the distribution areas, and distribution time bands. Also, in the present embodiment, it is determined by whether there is freedom of selection of the time limit of distribution based on a designated distribution time limit, usage conditions of communication resources based on a positional relationship with the terminal base station of a terminal station 30_{-j}, etc.

Also, the contents server 10, regardless of existence of a distribution request, suitably detects a communication state of the network system 1, that is, a traffic load (traffic load), and estimates a traffic load for different time bands.

Also, the server sets the communication expenses for when distributing information based on the estimated traffic load. The communication expenses is set by for example region, by time bands, by time bands for individual regions, etc.

Information of the estimated traffic load, communication expenses, etc. is stored in the contents server 10 and referred to at the time of determining the distribution period of time of the requested information. In addition, in some cases, it is transmitted to the terminal station 30_{-j} in advance and referred to at the time when a user requests distribution.

The network nodes 20_{-i} are relay devices for substantially connecting the contents server 10 and the terminal stations 30_{-j} in accordance with a predetermined network topology. In Fig. 3, the layer of the network nodes 20_{-i} forming the relay layer is made one layer for simplifying the figure, however, in an actual cellular wireless communication system 1, it is configured to have a plurality of layers.

The network nodes 20_{-i} suitably send distribution requests of information from the terminal stations 30_{-j} to the contents server 10 and distribute information from the contents server 10 to the terminal stations 30_{-j}.

The terminal stations 30_{-j} are terminal apparatuses comprised of cellular phones in the cellular wireless communication system 1 of the present embodiment. They are used by users for requesting distribution of information from the contents server 10 and performing mutual communication.

The configuration of the terminal stations 30_{-j} will be explained in detail with reference to Fig. 2.

Figure 2 is a block diagram of the configuration of a terminal station 30_{-j}.

A terminal station 30_{-j} comprises a signal transceiver 31, a cellular controller 32, an information controller 33, a storage 34, a display/command input

portion 35, a power supply circuit 36, and a timer 37.

Figure 4 is a block diagram of the configuration of the contents server 10.

The contents server 10 is comprised of a CPU (central processing unit) 11, ROM (read only memory) 12, RAM (random access memory) 13, frame memory 14, display 15, input device 16, external storage 17, communications I/F (interface) 18, and bus 19.

The CPU 11 controls the contents server 10 based on a processing program stored in the ROM 12.

The ROM 12 has a processing program for processing in the CPU 11. It stores a processing program in accordance with the information distribution routine explained below. The processing program is comprised of control instructions for processing for judging if a request for information content has been received from a terminal station 30_{-j} based on that request, processing for generating a response to the terminal 30_{-j} based on the result of judgment, processing for scheduling distribution of the information contents, processing for distributing the information contents to the terminal 30_{-j}, processing for charging the terminal station 30_{-j} along with the distribution of information, etc.

The RAM 13 stores temporary processing data when the CPU 11 is processing.

The frame memory 14 stores the display data processed at the CPU 11. The display 15 is an apparatus for displaying the display data stored in the frame memory 14 and provides the necessary information to the manager of the contents server 10. The input device 16 inputs necessary information from the manager of the contents server 10.

The external storage 17 is a randomly accessible information storage medium such as a magnetic disk or optical disk and stores a plurality of information contents.

The communications I/F 18 is a communications interface for connecting the contents server 10 to the network 20_{-j} through a communications line and connecting it to the terminal stations 30_{-j} through the network 20_{-j}. The contents server 10 transmits information contents and various control signals to the terminal stations 30_{-j} using the communications I/F 18.

The bus 19 connects circuits comprising the above contents server 10 for the transmission of programs or data.

Note that the processing program of the present embodiment was comprised to be stored in the ROM 12, but may also be stored in the external storage 17 and be transferred through the bus 19 to the RAM 13 at the time

of execution for execution by the CPU 11. Further, the communication I/F 18 may be comprised to be able to transmit and receive signals. The processing program may be received through a transmission line from an external terminal apparatus at the communication I/F 18, stored in the RAM 13 or external storage 17, and executed at the CPU 11.

That is, the contents server 10 may be loaded with the computer program for performing the above processing from a medium comprised of a magnetic disk, CD-ROM, or other information storage medium and also load it through the Internet, digital satellite, or other transmission medium for processing at the CPU 11.

Figure 5 is a block diagram of the configuration of a terminal apparatus 30_{-j}.

A terminal station 30_{-j} comprises a signal transceiver 31, a cellular controller 32, an information controller 33, a storage 34, a display/command input portion 35, a power supply circuit 36, and a timer 37.

The signal transceiver 31 is a circuit for performing signal processing for communicating with a base station and generates and sends a communication signal of a desired protocol based on control by the cellular controller 32. Further, the transceiver decodes the received signal to a predetermined base band signal

and outputs it to the information controller 33 under the control of the cellular controller 32.

The cellular controller 32 controls the signal transceiver 31 so as that the terminal stations 30_{-j} can suitably communicate in accordance with a predetermined protocol or supports the parts of the terminal stations 30_{-j} so as to be able to suitably maintain the conditions of the terminal stations 30_{-j} relating to the communication by functions provided to the communication system. For example, the cellular controller 32 detects whether or not a terminal station 30_{-j} is in an area able to communicate with the base station, namely, performs processing for detecting whether it is within a communication zone or outside the communication zone and outputting the results to the display/command input portion 35.

The information controller 33 performs desired processing on information received via the signal transceiver 31 and information set by a user via the display/command input portion 35.

The information controller 33 generates data requesting distribution of desired information based on user operation and outputs it to the signal transceiver 31.

Also, the information controller 33 stores a variety

of notice information etc. received from the contents server 10 in the storage 34 in accordance with need and displays it on the display/command input portion 35 so that a user can confirm it. The information of the scheduled point of time of distribution from the contents server 10 for an information distribution request transmitted to the contents server 10, the communication costs by region/by time bands suitably distributed from the contents server 10, and other data are stored in the storage 34 and displayed at the display/command input portion 35.

Further, the information controller 33 stores the information distributed from the contents server 10 to the storage 34, notifies a user that the information was received via the display/command input portion 35, and, based on an operation of the user, successively reads the information from the storage 34 and displays it at the display/command input portion 35.

Furthermore, when a scheduled period of time of distribution of the information is transmitted from the contents server 10 and the power supply of a terminal station 30_{-j} is turned off at the scheduled period of time, the information controller 33 sets a scheduled period of time to the timer 37 so that the power supply automatically turns on.

The storage 34 is a compact storage storing a variety of information notified or distributed by the contents server 10, information set by a user via the display/command input portion 35, etc. and is suitably accessed by the information controller 33. Specifically, the storage 34 is realized by a compact hard disk drive (HDD), an MD, a re-writeable CD, compact MO, flash memory, etc.

The display/command input portion 35 is an interface between an internal circuit of the terminal station 30_{-j} and a user and comprises a liquid crystal display panel for displaying information for the user, a speaker for outputting the information by audio, and a key board for the user to operate.

The power supply circuit 36 is a circuit for supplying power to the portions of a terminal station 30_{-j}.

Usually, the supply and cut-off of power by the power supply circuit 36 is performed directly by the user via the display/command input portion 35, however, the power supply circuit 36 of the present embodiment may be operated to supply and cut-off the power also by a signal from the timer 37. As a result, functions of automatic supply of power at the scheduled period of time of distribution of information from the contents server 10

and automatic cut-off of the power after receiving information are realized.

The timer 37 is a timing means for constantly measuring the time and outputs a control signal for the automatic supply and cut-off of power at the power supply circuit 36 based on a time set by the information controller 33.

Next, the operation of such a cellular wireless communication system 1 and the actual procedure of information distribution will be explained.

Figure 6 shows a basic procedure of information distribution in the present invention.

A terminal station 30_{-j} transmits information for demanding distribution of certain information contents to the contents server 10 (demand for contents). The information includes, in addition to terminal information including an ID for specifying the terminal station 30_{-j} and demanded content information expressing the content of the information contents requested, time limit information expressing the deadline for distribution of the information, that is, the time limit of distribution. The request information is transferred to the contents server 10 via a network node (CS) 20.

The contents server 10 receives the request information transmitted from the terminal station 30_{-j},

verifies the terminal station 30_{-j} and, when completes this normally, checks whether or not the requested information can be distributed under the demanded conditions. That is, it judges if it has the requested information contents and judges if it can distribute the information contents by the time indicated by the time limit for distribution.

Then, when the requested information is able to be provided, the terminal station 30_{-j} is notified that the demand was received (ACK).

Next, the contents server 10 estimates the time band where the traffic load is small in the communication system in the period until the deadline of the information distribution in the demand and again pages the terminal station 30_{-j} requesting the distribution of the information contents. If the terminal station 30_{-j} is in a state able to receive the information contents (ACK), it transmits the requested information contents via the network node 20_{-i} to the terminal station 30_{-j}.

When the terminal station 30_{-j} normally completes reception of the information contents, it transmits an acknowledgment to the effect of completing the reception (ACK) to the contents server 10, whereby all procedures of transmission and reception end.

Second Embodiment

Several modes of information distribution will be explained next.

First, a mode where the contents server 10 notifies the terminal servers 30_{-j} in advance of the time band for transfer of information contents as explained above will be explained.

In this case, the ACK signal sent from the contents server 10 to a terminal server 30_{-j} for a demand for information distribution includes information of the time band during which the contents server 10 will transmit the information contents to the terminal station 30_{-j} demanding distribution.

The contents server 10 which received the demand for information distribution from the terminal station 30_{-j} calculates the time band estimated to have less communications traffic during the time until the informed deadline based on results of operations up to then and the transmission schedule of the information contents received until then. Then, it includes the information of the scheduled point of time of distribution determined based on the calculated time band in the above ACK.

By the transfer of the ACK to the terminal station 30_{-j}, it is possible for the terminal station 30_{-j} to learn when the information will be distributed.

The terminal station 30_{-j} displays the point of time

scheduled for distribution of the information contents to the user and makes the user prepare for receiving the information contents during the time band.

Then, the contents server 10 again pages the terminal station 30_{-j} at the point of time notified in advance to the terminal station 30_{-j} and distributes the information contents by the above procedure.

In the above mode of transfer of information contents, the power supply of the terminal station 30_{-j} may be controlled in accordance with the point of time of transfer of the information contents.

A terminal station 30_{-j} is provided internally with a timer 37 which is constantly in operation even when the power supply of the terminal station 30_{-j} is turned off.

Therefore, when the power supply of the terminal station 30_{-j} is turned off at the scheduled point of time of distribution of the information contents notified by the contents server 10, the timer 37 outputs a trigger signal to the power supply circuit 36 to automatically turn on the power supply of the terminal station 30_{-j} and give the initial settings required for receiving the information contents transmitted from the contents server 10.

The contents server 10 transmits in the same way as the above the information contents demanded to be

distributed to the terminal station 30_{-j} when the point of time notified in advance arrives, so the terminal station 30_{-j} receives the same.

By configuring the terminal station in the above way, it becomes possible to turn off the power supply in usual times to keep down the power consumption and to automatically turn it on at the scheduled point of time of distribution of the information contents.

Further, the terminal station 30_{-j} may be configured to automatically turn off again when normally completing the reception of the information contents scheduled to be distributed.

Third Embodiment

Next, a mode of receiving information contents by a user designating a time band and region will be explained.

First, the contents server 10 or the network node 20_{-i} averages and calculates the traffic load in the past for different regions in advance. For example, it sets the relay area of a network node 20_{-i} as a calculated region. Alternatively, it sets an area comprised by relay areas of several network nodes 20_{-i} as the calculated region. Then, the contents server 10 or the network node 20_{-i} suitably predicts a traffic load by region and by time band based on the schedule of distributing the

information contents scheduled until then and calculation of the traffic load and, based on this prediction, calculates communication fees for the respective regions/time bands.

The communication fees for each region/time band are broadcasted to the terminal stations 30_{-1} to 30_{-m} using a BCCH (broadcast control channel) for simultaneous broadcast of control signals from a base sation to terminal stations in cellular wireless communications.

The terminal stations 30_{-j} suitably receive the information of the communication fees for each region/time band and store it in the storage 34 when performing processing (such as cell searching) necessary for connecting with the network.

Then, they display the information relating to the communication charges on the display/command input portion 35 when a user inputs an instruction to the effect of desiring to demand distribution of information contents etc. from the display/command input portion 35.

When an instruction of "in which time band and region the reception of the information contents is desired" is input by a user through the display/command input portion 35, a terminal station 30_{-j} generates region/time band information based on the input region and time band instruction, adds it to the demand for

distribution of information contents, and sends the result to the contents server 10.

The contents server 10 receiving this transmits an ACK by the above procedure to notify the terminal station 30_{-j} that the demand was received when the content of the demand for information distribution is acceptable.

Next, the contents server 10 pages the terminal station 30_{-j} in the region and time band designated by the terminal station 30_{-j} and transmits the demanded information contents when the terminal 30_{-j} responds. That is, it confirms if there is a terminal station 30_{-j} existing in the region designated by the user and where there is transmits the information contents to the terminal station 30_{-j} through the network node 20_{-i} positioned in the designated region.

Note that when the terminal station 30_{-j} does not respond to the paging, the contents server 10 tries again several times, then gives up distributing the information contents.

To avoid such giving up of distribution of the information contents as much as possible, information indicating a plurality of candidates for "in which time band and region reception of information contents is desired" transmitted from a terminal station 30_{-j} to the contents server 10 may be also set. Further, priority may

be added as well to the thus set plurality of candidates.

In this case, it is sufficient that the contents server 10 distribute the information contents in one of the region/time band among the candidates. Specifically, the contents server 10 tries to distribute the information contents for example from the one having the earliest time band among the candidates. When the candidate time bands are the same, it tries to distribute the information contents from the ones having the higher priorities.

Further, when the terminal station 30_{-j} does not respond to the paging in the designated region in the designated time band, the contents server 10, as a next stage, may refer to an HLR (home location register) storing information of the terminal stations 30_{-j} provided in the cellular wireless communications system 1 and page a region where the terminal station 30_{-j} is considered to exist. In this case, when the terminal station 30_{-j} responds to the paging, a fee is charged for the traffic load of that region/time band.

Note that the paging referring to the HLR may also be performed without paging in the designated region.

Fourth Embodiment

Next, a mode will be explained where at the time of the above information distribution, a charge for the

distribution of the same information is changed in accordance with time limit of distribution.

A terminal station 30_{-j} is comprised to be able to select one of the time limits of distribution of "receive distribution of information immediately" and "receive distribution of information before deadline" when sending a demand for distribution of information contents to the contents server 10.

When distribution of information is demanded immediately, the contents server 10 judges whether the demand is "OK" or "NG" by considering the current traffic load. When "OK", it sends the terminal station 30_{-j} ACK, while when "NG", it sends NACK.

When OK, the server immediately secures a communication line and distributes the information contents by using the existing method.

When NG, the server distributes NACK to notify that the information distribution is currently not possible. In response to this, the user sets an acceptable period of time etc. of the information distribution as a distribution time limit and issues a request for information distribution again.

In this case, the communication fee for the information distribution is determined by the period of time until the deadline of the information distribution.

Namely, the fee related to the distribution is the highest when the information is distributed immediately and becomes lower the later the information distribution time.

As explained above, according to the cellular wireless communication system 1 of the present invention, since it becomes possible not to provide information by real-time the distribution of information content can be scheduled for any period of time until the time limit for distribution, the traffic load in the time bands where the traffic load is high can be cut and the traffic load in time bands scarcely used before can be increased, so it becomes possible to obtain the effects of averaging the traffic load in terms of time and to effectively utilize communication facilities owned by a network operator fully for 24 hours as shown in Fig. 7.

Note that in Fig. 7, the traffic load shown by a thick line is a part indicating the traffic load of the communication system according to the present invention.

Also, due to this, since the network operator can much more effectively utilize the communication facilities, it becomes possible to lower the traffic load at peak times and reduce the communication costs.

Also, users of terminal stations become able to decide the deadline for information distribution by

themselves.

Namely, it becomes possible to finalize the point of time for information distribution in a user-led manner. As a result, it becomes possible for a user to receive information contents at the desired period of time at a reasonable communication cost by considering the point of time for information distribution and the communication charges necessary for the information distribution.

Note that the present invention is not limited to the embodiments and may be modified in various ways.

For example, the configurations of the terminal stations 30_{-j} etc. are not limited to above examples. Any configurations are possible.

For example, as a modification according to the present invention, the terminal station 30_{-j} may estimate the size of the information contents desired by a user and calculate and display to the user by about how much time and communication charge reception of the information contents would be possible from the size of the contents and a communications capacity able to be provided by the current system. Note that the size of the information contents may be estimated independently by the terminal station 30_{-j} in some cases, or the size of the information contents desired by the user may be obtained after demanding the contents server 10 notify

the size of the information contents in other cases.

Further, in the cellular wireless communication system 1, the contents server 10 or the network nodes 20_i may inform users through the BCCH of up to how much a load of communications can be provided at the present in the region, and the terminal stations 30_j may receive the information constantly and store it in a built-in storage for display to the users.

In addition, the configuration of the display/command input portion 35 was made a liquid crystal panel, a speaker, and a key board in the present embodiment, however, the portion may be configured, for example, without a key board and to comprise other any input/output means.

Also, the configuration of the storage 34 may use a recording device for recording information on any recording medium other than the above recording media and recording devices such as HD, MD, MO, CD, etc.

Also, the above embodiment was explained taking as an example the case where the configuration of a network was a cellular wireless communication system, however, the present invention is not limited to this and is able to be applied to any network systems.

Also, in the network of the present embodiment, only one contents server was shown, however, two or more

servers may exist as in usual cases. Also, the configuration of the network is not limited to the form in the above embodiment where a contents server, network nodes, and terminal stations are connected in a tree-structure. It may be any form of network.

As explained above, according to the embodiments of the present invention, an information distribution system and method capable of averaging a traffic load over time and effectively utilizing communication facilities can be provided.

Also, a terminal apparatus, a server apparatus, a data reception method, and a data transmission method able to be used in such an information distribution system and to contribute to averaging of the traffic load in the network and effective usage of communication facilities can be provided.

INDUSTRIAL APPLICABILITY

The present invention can be applied to various network systems such as cellular wireless communication systems.

CLAIMS

1. An information distribution system transmitting information based on a demand from a terminal apparatus from a server apparatus to the terminal apparatus,

said server apparatus comprising:

a first transceiver for transmission to the terminal apparatus; and

a first controller for scheduling a point of time for distribution based on a state of a communication line used for distribution of information in accordance with a request signal requesting information from the terminal apparatus received at said transceiver and controlling the system for distribution of information for said request signal to the terminal apparatus through the transceiver at the scheduled point of time, and

said terminal apparatus comprising:

a second transceiver for communication with a server apparatus; and

a second controller for generating a request signal for requesting the distribution of desired information, controlling the system for transmission of the requested information to said server through said second transceiver, and controlling the system for reception of said information distributed by said server apparatus in a period of time determined by said server

apparatus with respect to said request signal.

2. An information distribution system as set forth in claim 1, wherein

said second controller of said terminal apparatus generates a signal including time limit information indicating a time limit for distribution of said information as a request signal, and

said first controller of said server apparatus schedules the point of time for distribution of information based on the time limit for distribution designated by said terminal apparatus and a state of a communications line.

3. An information distribution system as set forth in claim 2, wherein the first controller of said server apparatus detects a traffic load of said communication line and distributes the information at a period of time when the traffic load is small.

4. An information distribution system as set forth in claim 3, wherein

said terminal apparatus further comprises an interface for providing information to a user, and estimates a period time until the time limit of distribution and a point of time when the traffic load is small, controls the system for notification of said estimated point of time to said terminal apparatus, and

schedules so as to distribute the information at the estimated point of time, and

said second controller of said terminal apparatus controls the system for provision of the point of time of distribution notified from the server apparatus to the user through the interface.

5. An information distribution system as set forth in claim 2, wherein said first controller of said server apparatus calculates an amount of charge for distribution of information based on a length of the period of time until the time limit of distribution designated by the terminal apparatus and performs processing for charging the terminal apparatus based on the calculated amount of charge.

6. An information distribution system as set forth in claim 2, wherein said second transceiver of said terminal apparatus communicates with the server through a wireless transmission base station.

7. An information distribution system as set forth in claim 6, wherein said first controller of said server apparatus calculates an amount of charge for distribution of information based on an efficiency of use of a communication resource in communication between said terminal apparatus and said base station and performs processing for charging the terminal apparatus based on

the calculated amount of charge.

8. An information distribution system as set forth in claim 1, wherein

said first controller of said server apparatus calculates cost information indicating communication costs based on a state of said communication line by region, by time band, or by time band for individual regions and controls the system for distribution of the calculated cost information to the terminal apparatus;

said second controller of said terminal apparatus generates, as said request signal, a signal including distribution information designating a desired region or time band or both desired for communication of information; and

said server apparatus schedules the system for distribution of information to the designated region and time band based on the request signal.

9. A terminal apparatus receiving distribution of information from a server apparatus,

said terminal apparatus receiving distribution of information from a server apparatus comprising:

a transceiver for transmission to the server apparatus; and

a controller for generating a request signal for requesting the distribution of desired information,

controlling the system for transmission of the requested information to said server through said transceiver, and controlling the system for reception of said information distributed by said server apparatus in a period of time determined by said server apparatus with respect to said request signal.

10. A terminal apparatus as set forth in claim 9, wherein said controller generates a signal including time limit information indicating a time limit for distribution of said information as a request signal.

11. A terminal apparatus as set forth in claim 10, further comprising an interface for providing information to a user, and

wherein the controller controls the system for provision of the point of time of distribution notified from the server apparatus to the user through the interface.

12. A terminal apparatus as set forth in claim 10, wherein said transceiver communicates with the server through a wireless transmission base station.

13. A terminal apparatus as set forth in claim 9, wherein said controller generates, as said request signal, a signal including distribution information designating a desired region or time band or both desired for communication of information.

14. A terminal apparatus as set forth in claim 13, further comprising an interface for providing information to a user, and

wherein said controller controls the system for provision to the user through the interface of cost information based on a state of said communication line by region, by time band, or by time band for individual regions as received from the server apparatus.

15. A terminal apparatus as set forth in claim 10, further comprising an interface for providing information to a user, and

wherein said terminal apparatus controls the system for provision to the user through the interface of a period of time until a time limit of distribution and time band where the traffic load of the communication line is small notified from the server apparatus.

16. A terminal apparatus as set forth in claim 9, further comprising

a counter for counting a period of time;

a power supply for controlling the supply of power to each portion of the terminal apparatus and substantially making each portion valid or invalid; and

a storage for storing information, and

said controller receiving a scheduled point of time at which said information is to be distributed as

notified by said server apparatus, stores said received scheduled period of time of distribution in said storage, starts the supply of power from said power supply and receives information distributed from said server apparatus when the parts of the terminal apparatus are invalid in state near the scheduled period of time of distribution based on the scheduled point of time of distribution stored in said storage and the measured period of time.

17. A terminal apparatus as set forth in claim 16, wherein said controller stops the supply of power from said power supply and makes the parts of the terminal apparatus invalid in state when the reception of information distributed from said server apparatus ends.

18. A server apparatus transmitting information based on a demand from a terminal apparatus,

said server apparatus comprising:

a transceiver for transmission to the terminal apparatus; and

a controller for scheduling a point of time for distribution based on a state of a communication line used for distribution of information in accordance with a request signal requesting information from the terminal apparatus received at said transceiver and controlling the system for distribution of information for said

request signal to the terminal apparatus through the transceiver at the scheduled point of time.

19. A server apparatus as set forth in claim 18, wherein an internal controller schedules the point of time for distribution of information based on time limit information indicating a time limit for distribution of said information included in said request signal and the state of a communication line.

20. A server apparatus as set forth in claim 19, wherein the controller detects a traffic load of said communication line and distributes the information at a period of time when the traffic load is small.

21. A server apparatus as set forth in claim 20, wherein said controller estimates a period of time until the time limit of distribution and a point of time when the traffic load is small, controls the system for notification of said estimated point of time to said terminal apparatus, and schedules distribute the information at the estimated point of time.

22. A server apparatus as set forth in claim 18, where said controller calculates an amount of charge for distribution of information based on a length of the period of time until the time limit of distribution designated by the terminal apparatus and performs processing for charging the terminal apparatus based on

the calculated amount of charge.

23. A server apparatus as set forth in claim 18, where said controller calculates an amount of charge for distribution of information based on an efficiency of use of a communication resource in communication between said terminal apparatus and said base station and performs processing for charging the terminal apparatus based on the calculated amount of charge.

24. A server apparatus as set forth in claim 18, where said controller calculates cost information indicating communication costs based on a state of said communication line by region, by time band, or by time band for individual regions and controls the system for distribution of the calculated cost information to the terminal apparatus and schedules distribution of information to the designated region and time band based on the request signal.

25. An information distribution method for transmitting information based on a request from a terminal apparatus from a server apparatus to the terminal apparatus,

said information distribution method for transmitting information based on a request from a terminal apparatus from a server apparatus to the terminal apparatus, comprising the steps of:

having said terminal apparatus generates a request signal requesting distribution of desired information;

transmitting said request signal from said terminal apparatus to said server;

having said server apparatus schedule a point of time for distribution based on a state of a communication line to be used for the distribution of information in accordance with a request signal requesting information from said terminal apparatus;

distributing information for said request signal from said server apparatus to said terminal apparatus at the scheduled point of time; and

having said terminal apparatus receive said information distributed from said server apparatus.

26. An information distribution method as set forth in claim 25, wherein:

said request signal is a signal including time limit information indicating a time limit of distribution of said information, and

said server apparatus schedules a point of time for distribution of the information based on the time limit information of said request signal and a state of a communication line.

27. An information distribution method as set forth

in claim 26, wherein said server apparatus detects a traffic load of said communication line and schedules distribution of said information for a period of time where the traffic load is small

28. An information distribution method as set forth in claim 26, wherein, when receiving said request signal, said server apparatus estimates a period of time until the time limit for distribution and a point of time where the traffic load is small, notifies the estimated point of time to said terminal apparatus, and distributes the information at the estimated point of time.

29. An information distribution method as set forth in claim 27, wherein said server apparatus calculates an amount of charge for distribution of information based on a length of the period of time until the time limit of distribution designated by the terminal apparatus and performs processing for charging the terminal apparatus based on the calculated amount of charge.

30. An information distribution method as set forth in claim 26, wherein said terminal apparatus communicates with the server through a wireless communication base station.

31. An information distribution method as set forth in claim 30, wherein said server apparatus calculates an amount of charge for distribution of information based on

an efficiency of use of a communication resource in communication between said terminal apparatus and said base station and performs processing for charging the terminal apparatus based on the calculated amount of charge.

32. An information distribution method as set forth in claim 25, wherein:

said server apparatus calculates cost information indicating communication costs based on a state of said communication line by region, by time band, or by time band for individual regions and distributes the calculated cost information to the terminal apparatus;

said terminal apparatus generates a signal including distribution information designating a region or time band or both desired for distribution of information; and

said server apparatus schedules distribution of information to the designated region and time band based on the request signal.

33. A data reception method for receiving distribution of information from a server apparatus,

said data reception method for receiving distribution of information from a server apparatus, comprising the steps of:

generating a request signal requesting distribution of desired information;

transmitting said requested information to said server; and

receiving said information distributed by said server apparatus in a period of time determined by said server apparatus for said request signal.

34. A data reception method as set forth in claim 33, further comprising a step of generating a signal including time limit information indicating a time limit for distribution of said information as said request signal.

35. A data reception method as set forth in claim 33, further comprising a step of generating a signal including distribution information designating a desired region or time band or both for distribution of information as said request signal.

36. A data reception method as set forth in claim 35, further comprising a step of receiving from said server apparatus cost information indicating communication costs based on a state of said communication line by region or by time band or by time band for individual regions.

37. A data reception method as set forth in claim 34, further comprising a step of providing the user with

a period of time until said time limit of distribution and point of time where the traffic load of the communication line is small as notified from said server apparatus.

38. A data reception method as set forth in claim 33, further comprising the steps of:

receiving a scheduled point of time for distribution of information from said server apparatus and

controlling a power supply of a receiver to enable reception of information distributed from said server apparatus near the scheduled period of time of distribution based on the received scheduled point of time of distribution and an internally measured period of time.

39. A data reception method as set forth in claim 38, further comprising a step of controlling the power supply of the receiver to cut the supply of power to at least part of the circuits of the receiver when it finishes receiving the information distributed from said server apparatus.

40. A data transmission method for transmitting information based on a request from a terminal apparatus,

said data transmission method for transmitting information based on a request from a terminal apparatus,

comprising the steps of:

receiving a request signal requesting information from a terminal apparatus;

scheduling a point of time for distribution based on a state of a communication line used for distribution of information; and

transmitting the information for the request signal to the terminal apparatus at the scheduled point of time.

41. A data transmission method as set forth in claim 40, further comprising a step of scheduling the point of time for distribution of information based on time limit information indicating a time limit of distribution of information included in said request signal and the state of the communication line.

42. A data transmission method as set forth in claim 41, further comprising a step of detecting a traffic load of said communication line and scheduling distribution of said information in a period of time where the traffic load is small.

43. A data transmission method as set forth in claim 42, further comprising the steps of, when receiving said request signal, estimating a period of time until said time limit of distribution and point of time where the traffic load is small, notifying said estimated point

of time to said terminal apparatus, and scheduling distribution of said information at the estimated point of time.

44. A data transmission method as set forth in claim 40, further comprising a step of calculating an amount of charge for distribution of information based on a length of the period of time until the time limit of distribution and performing processing for charging the terminal apparatus based on the calculated amount of charge.

45. A data transmission method as set forth in claim 40, further comprising a step of calculating an amount of charge for distribution of information based on an efficiency of use of a communication resource in communication between said terminal apparatus and a wireless communication base station and performing processing for charging the terminal apparatus based on the calculated amount of charge.

46. A data transmission method as set forth in claim 40, further comprising a step of calculating cost information indicating communication costs based on a state of said communication line by region, by time band, or by time band for individual regions and distributing the calculated cost information to the terminal apparatus.

47. A data transmission method as set forth in claim 46, further comprising a step of scheduling distribution of information to a region and time band included in a request signal from said terminal apparatus.

ABSTRACT

An information distribution system and method capable of averaging a traffic load over time and effectively utilizing communication facilities, wherein a terminal station 30 transmits to a contents server 10 a distribution request for desired information including information of time limit of distribution, and the contents server 10 receives the distribution request, estimates a time band where the traffic load is small in the communications system in the period until the time limit of distribution, pages the terminal station again at that period of time, and, if the terminal station is in a state able to receive the information content, transmits the requested information content to the terminal station 30 through a network node.

FIG. 1


SEARCH
DEMAND
CONTENTS
TIME
(CONTENTS SERVER)
DEMAND FOR
CONTENTS
REQUESTED
CONTENTS
TIME
(NETWORK NODE)
DEMAND FOR
CONTENTS
REQUESTED
CONTENTS
TIME
(TERMINAL STATION)

FIG. 2



FIG. 3


CONTENTS SERVER
10
NETWORK NODE
20-1
NETWORK NODE
20-i
NETWORK NODE
20-m
TERMINAL STATION
30-1
TERMINAL STATION
30-i
TERMINAL STATION
30-m
1

FIG. 4


10
CPU
11
ROM
12
RAM
13
FRAME MEMORY
14
DISPLAY
15
INPUT DEVICE
16
EXTERNAL STORAGE
17
COMMUNICATIONS I/F
18
TO COMMUNICATIONS LINE
19

FIG. 5


POWER SOURCE CIRCUIT
32
31
CELLULAR CONTROLLER
SIGNAL TRANSCEIVER
36
TIMER
33
37
DISPLAY/COMMAND INPUT PORTION
INFORMATION CONTROLLER
35
34
30-j

FIG. 6



FIG. 7



LIST OF REFERENCE NUMERALS

1... cellular wireless communication system

10.. contents server

20... network node

30... terminal station

31... signal transceiver

32... cellular controller

33... information controller

34... storage

35... display/command input portion

36... power supply circuit

37... timer

Declaration and Power of Attorney for Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

私は、以下に記名された発明者として、ここに下記の通り宣言する：

As a below named inventor, I hereby declare that:

私の住所、郵便の宛先そして国籍は、私の氏名の後に記載された通りである。

My residence, post office address and citizenship are as stated next to my name:

下記の名称の発明について、特許請求範囲に記載され、且つ特許が求められている発明主題に関して、私は、最初、最先且つ唯一の発明者である（唯一の氏名が記載されている場合）か、或いは最初、最先且つ共同発明者である（複数の氏名が記載されている場合）と信じている。

____

____

I believe I am the original, first and sole inventor if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled.

INFORMATION DISTRIBUTION SYSTEM AND METHOD, TERMINAL APPARATUS, SERVER APPARATUS, DATA RECEPTION METHOD, AND DATA TRANSMISSION METHOD

上記発明の明細書はここに添付されているが、下記の欄がチェックされている場合は、この限りでない：

☐ __________ の日に出願され、
この出願の米国出願番号またはＰＣＴ国際出願番号は、
__________ であり、且つ
__________ の日に補正された出願（該当する場合）

the specification of which is attached hereto unless the following box is checked:

☒ was filed on February 9 2000
as United States Application Number of
PCT International Application Number PCT/JP00/00705
_____ and was amended on
_____ (if applicable).

私は、上記の補正書によって補正された、特許請求範囲を含む上記明細書を検討し、且つ内容を理解していることをここに表明する。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第３７編規則１．５６に定義されている、特許性について重要な情報を開示する義務があることを認める。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration

日本語宣言書

私は、ここに、以下に記載した外国での特許出願または発明者証の出願、或いは米国以外の少なくとも一国を指定している米国法典第３５編第３６５条(a)によるＰＣＴ国際出願について、同第１１９条(a)-(d)項又は第３６５条(b)項に基づいて優先権を主張するとともに、優先権を主張する本出願の出願日よりも前の出願日を有する外国での特許出願または発明者証の出願、或いはＰＣＴ国際出願については、いかなる出願も、下記の枠内をチェックすることにより示した。

Prior Foreign Application(s)

外国での先行出願

11-032065 (Number) （番号）	Japan (Country) （国名）	9 February 1999 (Day/Month/Year Filed)	☐
PCT/JP00/00705 (Number) （番号）	PCT (Country) （国名）	9 February 2000 (Day/Month/Year Filed)	☐
(Number) （番号）	(Country) （国名）	(Day/Month/Year Filed)	☐
(Number) （番号）	(Country) （国名）	(Day/Month/Year Filed)	☐
(Number) （番号）	(Country) （国名）	(Day/Month/Year Filed)	☐
(Number) （番号）	(Country) （国名）	(Day/Month/Year Filed)	☐

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT international application having a filing date before that of the application for which priority is claimed.

Priority Not Claimed

優先権主張なし

私は、ここに、下記のいかなる米国仮特許出願についても、その米国法典第３５編１１９条(e)項の利益を主張する。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.) （出願番号）	(Filing Date) （出願日）

私は、ここに、下記のいかなる米国出願についても、その米国法典第３５編第１２０条に基づく利益を主張し、又米国を指定するいかなるＰＣＴ国際出願についても、その同第３６５条(c)に基づく利益を主張する。また、本出願の各特許請求の範囲の主題が、米国法典第３５編第１１２条第１段に規定された態様で、先行する米国出願又はＰＣＴ国際出願に開示されていない場合においては、その先行出願の出願日と本国内出願日またはＰＣＴ国際出願日との間の期間中に入手された情報で、連邦規則法典第３７編規則１．５６に定義された特許性に関わる重要な情報について開示義務があることを承認する。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365© of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

(Application No.) （出願番号）	(Filing Date) （出願日）	(Status: Patented, Pending, Abandoned) （現況：特許許可、係属中、放棄）

私は、ここに表明された私自身の知識に係わる陳述が真実であり、且つ情報と信ずることに基づく陳述が、真実であると信じられることを宣言し、さらに、故意に虚偽の陳述などを行った場合は、米国法典第１８編第１００１条に基づき、罰金または拘禁、若しくはその両方により処罰され、またそのような故意による虚偽の陳述は、本出願またはそれに対して発行されるいかなる特許も、その有効性に問題が生ずることを理解した上で陳述が行われたことを、ここに宣言する。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both. under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

日本語宣言書

委任状： 私は本出願を審査する手続を行い、且つ米国特許商標庁との全ての業務を遂行するために、記名された発明者として、下記の弁護士及び／または弁理士を任命する。（氏名及び整理番号を記載すること）

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact al business in the Patent and Trademark Office connected therewith (list name and registration number)

(2) WILLIAM S. FROMMER, Registration No. 25,506 and
DENNIS M. SMID, Registration No. 34,930

書類送付先

Send Correspondence to:
WILLIAM S. FROMMER, Esq.
c/o FROMMER LAWRENCE & HAUG LLP
745 Fifth Avenue
New York, New York 10151

直通電話連絡先：（氏名及び電話番号）

Direct Telephone Calls to: (212) 588-0800
To the attention of: **WILLIAM S. FROMMER**

唯一または第一発明者氏名

Full name of sole or first inventor

1-00 Kazuyuki SAKODA

発明者の署名 日付

inventor's signature Date

Kazuyuki Sakoda November 30, 2000

住所

Residence

~~Tokyo~~, Japan JPX

国籍

Citizenship

Japan

郵便の宛先

Post Office Address:

Sony Corporation
7-35 Kitashinagawa 6-Chome
Shinagawa-Ku, Tokyo 141, Japan

第二共同発明者がいる場合、その氏名

2-00 full name of second joint inventor, if any

Mitsuhiro SUZUKI

第二共同発明者の署名 日付

Second Inventor's signature Date

Mitsuhiro Suzuki November 30, 2000

住所

Residence

国籍

Chiba, Japan JPX

Citizenship

郵便の宛先

Japan

Post Office Address

Sony Corporation
7-35 Kitashinagawa 6-Chome
Shinagawa-Ku, Tokyo 141, Japan

（第三以下の共同発明者についても同様に記載し、著名をすること）

(Supply similar information and signature for third and subsequent joint inventors)